

TECHNICAL DATA : SMV 50-1200 C

LIFTING DATA			
Lifting capacity / Load center (up to 6 000 mm / standard mast)	kg / mm	50 000 / 1 200	
Lifting speed, unloaded / at rated load	m/s	0,21 / 0,16	
Lowering speed, unloaded / at rated load	m/s	0,4 / 0,4	
DRIVING DATA			
Drive speed forward, unloaded / at rated load	km/h	24 / 21	
Drive speed reverse, unloaded / at rated load	km/h	18 / 17	
Incline (driving ability) at rated load at 0 km/h/at 2 km/h	%	34 / 21	
Towing (power ability) at rated load at 0 km/h/at 2 km/h	kN	397 / 266	
SERVICE WEIGHT / AXLE PRESSURE			
Service weight	kg	58 100	
Axle pressure front, unloaded / at rated load	kg	30 500 / 101 700	
Axle pressure rear, unloaded / at rated load	kg	27 600 / 6 400	
ENGINE (electronic controlled)			
Engine make / model name		Volvo TAD-1171-VE	
Emission approval EU / US		Stage 4 / Tier 4f	
Monitoring / emission controlled / CanBus		Yes / yes / yes	
Fuel / type of engine / intercooler		Diesel/4-stroke/ yes	
Power ISO 3046 / max speed	kW / rpm	265 / 2 100	
Torque ISO 3046 / at speed	Nm / rpm	1 785 / 1 265	
Displacement / No. of cylinders / type	L / /	10,8 / 6 / Inline	
Fuel consumption, normal driving	L/h	15 – 17	
Alternator, type/power	W / Amp	AC / 3 080 / 110	
Starting battery, voltage/capacity	V / Ah	2 x 12 / 140	
TRANSMISSION (electronic controlled)			
Transmission make / model name		Dana TE-30	
Monitoring / reverse protection / CanBus		Yes / yes / yes	
Clutch, type		Torque converter	
Transmission type / type of shift gear		Softshift – Powershift / Automatic	
No. of gears, forward/reverse		5 / 3	
DRIVE AXLE & STEER SYSTEM			
Drive axle make / model name		Kessler D102	
Drive axle type / drive axle width	/ mm	Differential + hub reduction / 4 160	
Service brake system, type / affected wheels		Oil cooled Wet Disc Brakes / drive wheels	
Parking brake system, type / affected wheels		Dry disc brake / spring release / drive wheels	
STEER AXLE & STEER SYSTEM			
Steer axle make / type		Konecranes / double acting single cylinder	
Steering system		Hydraulic servo assisted / power steering	
WHEELS			
Number of wheels, front+rear / Type (*driven)		4*+2 / pneumatic	
Tire pressure front / rear	MPa	1,0 / 1,0	
Tire dimensions (Ply rating) front / rear	Inch (No)	18.00 x 25" (PR 40) / 18.00 x 25" (PR 40)	
Rim dimension front / rear	Inch	13.00 x 25" / 13.00 x 25"	
HYDRAULIC SYSTEM			
Hydraulic pump make / model name		Parker & Hannifin / P2-series	
Hydraulic system / pump type		Load sensing system / variable piston pump	
Power-on-demand / Low energy		Yes / yes	
Hydraulic oil pressure mast	MPa	19	
TANK VOLUMES			
Diesel tank volume	L	550	
Hydraulic tank volume	L	630	
LIFTING EQUIPMENT			
Lift mast make / model		Konecranes / Duplex standard	
Lift mast type / design		2-stage / free visibility	
Fork carriage make / model		Konecranes / integral double forks	
Fork carriage type		Hydraulic side shift & fork positioning	
OTHERS			
Noise level (inside Cab / Lm)	DIN 45635	dB(A)	71
Noise level (inside Cab/ LpAZ)	EN 12053	dB(A)	76
Noise level (outside at 7 m/ Lwa)	2005/88/EC	dB(A)	111
NORMS & STANDARDS			
Machine Directive in Europe	2006 / 42 / EC		Yes
Stability of Industrial Trucks	ISO 1074		Yes
Safety of Industrial Trucks	EN ISO 3691-1		Yes

